

Rugby®

TRAILER HOISTS

TB-12 & TB-14

NEW



www.rugbymfg.com



Member



TB-12 & TB-14 TRAILER HOISTS

NEW GAME CHANGING TRAILER HOISTS!

The new TB-12 and TB-14 trailer hoists come backed with 47 years of hoist engineering and manufacturing experience.

Rugby® is the industry leader in hoist design and testing.

All Rugby trailer hoists are tested for an extended life cycle, loaded at full-rated capacity*. This means Rugby trailer hoists are proven reliable before they even leave the building.

**Test assumes all recommended maintenance is adhered to.*


RUGBY HOIST SPECIFICATIONS for 45° Dump Angle		
	TB-12	TB-14
Hoist Type	Scissors	
Mounting Height (in.)	7	9
Minimum Vertical Height (in.)	8	10
"M" Dimension (in.)	77.25	79.25
Maximum Hydraulic Flow Rate (GPM)	6	6
Maximum "Up" Pressure (PSI)	3200	
Maximum "Down" Pressure (PSI)	1500	
Cylinder Bore & Stroke (in.)	5 x 16	5.5 x 16
Chromed Cyl. Shaft Diameter (in.)	2	2.25
Approx Weight (lbs)	275	325

RUGBY HOIST CAPACITY for 45° Dump Angle (in tons)		
Hoist Model and Overhang		
Body Length	TB-12	TB-14
10'	10.9	15.7
12'	8.5	11.8
14'	6.9	9.4
16'		7.8

Capacity based on water-level load.

Caution: The combined weights of trailer frame and body, hoist and load must not exceed the gross weight rating of any component.

Because of variations in applications, the data contained here is provided as a general guide. Rugby has an "Application Recommendation" program to ensure you select the appropriate hoist for your application. Contact Rugby for further details.



RUGBY MANUFACTURING

Rugby, ND • 701-776-5722 • FAX 701-776-6235
www.rugbymfg.com • E-mail sales@rugbymfg.com

a  **TBEI** company
TRUCK BODIES & EQUIPMENT INTERNATIONAL, Inc.

Sold by: